

Model		C6X8	C6X10	C6X11	C6X12	C6X14	C6X16	C6X20
		0	0	0	5	5	0	0
Feed opening length(mm)		800	1000	1100	1250	1450	1600	2000
Feed opening width(mm)		520	760	850	950	1100	1200	1500
Power KW(Kw)		75	110	160	160	200	250	400
Speed(rpm)		350	260	230	220	220	220	200
Dimension(mm)	Discharge opening(mm)	T/h	T/h	T/h	T/h	T/h	T/h	T/h
0-90	60	80-110						
0-105	70	70	100-135					
0-120	80	110-150	150-200	160-240				
0-135	90	130-175	170-220	180-260				
0-150	100	145-190	190-250	200-280	240-340			
0-185	125	180-245	235-310	250-360	280-410	320-470		
0-225	150	225-290	280-360	300-430	340-480	370-550	420-610	
0-260	175		330-420	340-490	370-550	430-630	470-700	620-890
0-300	200			380-550	420-620	480-710	530-790	690-1000
0-340	225				470-690	540-790	590-880	770-1100
0-375	250				520-760	600-870	650-970	850-1200

0-410	275					660-950	700-1060	930-1300
0-450	300						750-1100	1000-1500

**Notice:** Any change of European Type Jaw Crusher technical data shall not be advised additionally.