

Model	Cavity	Maximum feed size(mm)	CSS min-max(mm)	Capacity(tph)	Power KW(HP)	Dimension (L×W×H) (mm)	Weight (t)
HST100	S1(Extra Coarse)	240	22-38	85-170	90(125)	1535×1275×2710	9.6
	S2(Medium Coarse)	200	19-32	70-130			
HST160	S1(Extra Coarse)	360	25-54	120-345	132(175)	2045×1635×3040	15.5
	S2(Medium Coarse)	300	22-48	105-305			
	S3(Coarse)	235	19-48	90-275			
HST250	S1(Extra Coarse)	450	35-54	255-605	220(300)	2675×2550×3940	28
	S2(Medium Coarse)	400	29-51	215-515			
	S3(Coarse)	300	25-51	190-490			
HST315	S1(Extra Coarse)	560	41-76	335-1050	315(400)	3110×2945×4480	43.5
	S2(Medium Coarse)	500	38-70	305-895			
Model	Cavity	Maximum feed size(mm)	CSS min-max(mm)	Capacity(tph)	Power KW(HP)	Dimension (L×W×H) (mm)	Weight (t)
HST100	H1(Fine)	135	10-32	45-130	90(125)	1540×1280×2300	7.5
	H2(Medium Fine)	65	8-19	35-80			
	H3(Extra Fine)	38	4-16	27-60			
	H1(Fine)	185	13-38	66-210			10

HST160	H2(Medium Fine)	90	10-32	65-165	132(175)	2000×1550×2600	
	H3(Extra Fine)	50	6-25	48-105			
HST250	H1(Fine)	215	16-44	110-395	220(300)	2315×1830×2940	19.5
	H2(Medium Fine)	110	13-38	115-340			
	H3(Extra Fine)	70	8-32	90-255			
HST315	H1(Fine)	275	16-51	170-665	315(400)	2740×2200×3590	28.5
	H2(Medium Fine)	135	16-38	190-505			
	H3(Extra Fine)	65	13-22	205-320			
HST560	H1(Fine)	300	22-70	448-1331	560(750)	3300×2600×4463	51
	H2(Medium Fine)	155	19-70	400-1098			
	H3(Extra Fine)	80	10-44	280-669			
HST750	H1(Fine)	370	25-70	480-2500	630(850)	3800×3100×5305	80
	H2(Medium Fine)	195	22-70	552-1115			
	H3(Extra Fine)	80	10-51	364-790			